

Product overview

SENSOTEC Sensor Monoblock


MB HF2 DALI-2

110059685

SENSOTEC MB HF2 DALI-2



HF sensor with rod antenna for max. 8m detection range and DALI control with constant light control.



Technical specifications

Dimensions	65 × 40 × 42mm Hole spacing 71mm
3D data	available online
Features	Motion sensor, light sensor, feedback display, parameterization interface
Sensor technology	High-frequency technology, Rod antenna
Transmitter power	1 - 2mW
Transmitter frequency	5,8GHz
Light measurement range	2 - 2000lx
Angle of coverage	360° with 160° angle of aperture
Reach	max. Ø 8m for mounting height 4m
Network connection	220 - 240V, 50Hz
Power	max. 15 EVG
Supply current DALI-2	30mA guaranteed (15 EVG's), max. 250mA
Connection	0.5 - 2.5mm ²
IP rating	IP20
Protection class	II
Temperature range	-20 to +60°C (tc +60°C)
Interfaces	DALI-2
Approval marks / Conformity	CE
Configuration	Remote control RCS2, Remote control RCS4

Note: STEINEL Solutions AG hereby declares that the SENSOTEC Monoblock products comply with Directive 2014/53/EU. The full text of the EU Declaration of Conformity is available at the following link: [EU Declaration of Conformity](#)

Downloads & further details

[Data sheet Monoblock](#)[3D data](#)